## Publication pour la présente candidature LAFPT

Titre	A Novel Term Weighting Scheme Model		
Auteurs	Demba Kandé; Reine Marie Marone; Fodé Camara; Samba Ndiaye		
Référence	ICFET '18 Proceedings of the 4th International Conference on Frontiers of Educational Technologies		
Editeur	ACM		
Pages	92 - 96		
Année	2018		
DOI	10.1145/3233347.3233374		
URL	https://dl.acm.org/citation.cfm?doid=3233347.3233374		
Index	https://www.scopus.com/sourceid/11600154611		
ISBN	978-1-4503-6472-0		
Encadreur	oui		
Extrait d'une thèse	oui		

## Source details

### ACM International Conference Proceeding Series

Scopus coverage years: 1999, from 2002 to 2016

Publisher: ACM

Subject area: (Computer Science: Computer Vision and Pattern Recognition)

(Computer Science: Computer Networks and Communications ) (Computer Science: Software ) View all V

CiteScoreTracker 2018 ①

Last updated on 11 February, 2019 Updated monthly

Sitation Count 2018


2 749 Citations to date >

\* Documents 2015 - 2017

3 908 Documents to date >

SEARCH





Departement of mathematics, Cheikh Anta Diop University, Dakar, Senegal

Fodé Camara Department of mathematics, Alioune Diop University,

Bambey, Senegal

#### **Tools and Resources** Buy this Article 2018 Article Recommend the ACM DL Research to your organization Refereed limited Request Permissions TOC Service: <u>Bibliometrics</u> <u>Email</u> <u>₩ RSS</u> Citation Count: 0 Downloads (cumulative): 14 Downloads (12 Months): 14 Downloads (6 Weeks): 4 Save to Binder Export Formats: BibTeX EndNote ACM Ref Upcoming Conference: ICFET '18 Proceedings of the 4th International Conference on Frontiers of Educational LAK '19



Technologies Pages 92-96

Moscow, Russian Federation — June 25 - 27, 2018 ACM New York, NY, USA @2018 table of contents ISBN: 978-1-4503-6472-0 doi>10.1145/3233347.3233374

Author Tags -

Contact Us | Switch to single page view (no tabs)

**Activer Windows** Accédez aux paramètres pour activer Windows.

### A Novel Term Weighting Scheme Model

Demba Kandé, Reine Marie Marone, Samba Ndiaye

Departement of mathematics, Cheikh Anta Diop University, Dakar, Senegal E-mail:demba4.kande@ucad.edu.sn Fodé Camara
Department of mathematics, Alioune Diop University,
Bambey, Senegal
E-mail: fode.camara@uadb.edu.sn

#### **ABSTRACT**

The use of textual data has increased exponentially in recent years due to the networking infrastructure such as Facebook, Twitter, Wikipedia, Blogs, and so one. Analysis of this massive textual data can help to automatically categorize and label new content. Before classification process, term weighting scheme is the crucial step for representing the documents in a way suitable for classification algorithms. In this paper, we are conducting a survey on the term weighting schemes and we propose an efficient term weighting scheme that provide a better classification accuracy than those obtained with the famous TF-IDF, the recent IF-IGM and the others term weighting schemes in the literature.

#### **CCS Concepts**

• Information systems~Document representation

#### Keywords

Vector space model, classification, text mining, term weighting scheme.

#### 1. INTRODUCTION

In the recent years, web users generated a large amount of various and useful text information. This textual data from Facebook, Twitter, Wikipedia, Blogs, and so one can be analyzed to identify most informative comments, to get users' opinions from comments, to recognize a potentially spam content, etc.

Before classification, text documents must be represented in a way suitable for data mining algorithms. Thus, several term weighting schemes (also called vector space models) have been developed in the literature to improve the performance of text classification algorithms. These techniques can be divided into two approaches, unsupervised and supervised term weighting methods, depending on the use of the class label in training corpus. The pioneer works are the unsupervised weighting scheme, binary and the popularly-used TF-IDF [3]. The binary method tells when a term appears in

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from Permissions@acm.org.

ICFET '18, June 25–27, 2018, Moscow, Russian Federation © 2018 Association for Computing Machinery.

https://doi.org/10.1145/3233347.3233374

ACM ISBN 978-1-4503-6472-0/18/06...\$15.00

a document, and TF-IDF determines terms that are frequent in the document, but infrequent in the corpus.

However, the traditional unsupervised weighting scheme is not really useful for text classification tasks. As an alternative, various works have been done on weighting models based on the known class label, including, the recent TF-IGM scheme [9]. TF-IGM adopts a new statistical model to measure a term's class distinguishing power. To the best of our knowledge, it is the most efficient term weighting scheme.

This paper challenges TF-IGM [9], and introduce a new and efficient supervised term weighting scheme based on inertia contribution of document. Our weighting scheme has the benefit because it affects positively the classification performance. The experimental results show that our algorithm outperforms the famous TF-IDF, and the recent and efficient TF-IGM.

The rest of the paper is organized as follows. Section 2 discusses related works. In section 3, we give the details of our proposition. In Section 4, we evaluate the performance of our algorithm. Section 5 concludes the paper and gives some future works.

## 2. ANALYSES OF CURRENT TERM WEIGHTING SCHEMES

In the literature, various term weighting schemes have been proposed for text categorization (TC), and thus for optimizing the classifier accuracy. We have focused on the limitations of TF-IDF [3] and TF-IGM [9] and others, which are respectively the most used and the most efficient term weighting schemes.

We can explore the literature, through a simple example. Let's consider the following corpus, denoted d:

TABLE I AN SIMPLE EXAMPLE OF CORPUS D

Id document	Document contain	class
$d_1$	"the sky is blue"	negative
$d_2$	"the sun is bright today"	positive
$d_3$	"the sun in the sky is bright"	positive
$d_4$	"we can see the shining sun, the bright sun"	positive

Then, its dictionary is {'blue', 'sky', 'bright', 'sun', 'today', 'can', 'see', 'shining'}.

#### 2.1 Traditional Term Weighting Schemes

Traditional term weighting schemes are Binary (or Boolean), TF and TF-IDF weighting [2], which are originated from information retrieval. As the weight of a term, the term frequency (TF) in a document is obviously more precise and reasonable than the binary value, 1 or 0, denoting term presence or absence in the document because the topic terms or key words often appear in the document frequently and they should be assigned greater weights than the rare words. But term weighting by TF may assign large weights to the common words with weak text discriminating power.

To offset this shortcoming, a global factor, namely inverse document frequency (IDF), is introduced in the TF-IDF scheme.

$$w(t_j) = tf_{ij} \times log(\frac{N}{df_j})$$
 (1)

Where  $tf_{ij}$  denotes the frequency of term j in document i and N is the total number of documents and  $df_j$  is the number of documents that contains the term j.

The weight is composed of two factors: the local factor TF (for Term Frequency) metric that calculates the number of times a word appears in a document; and the global factor IDF (Inverse Document Frequency) term is computed as the logarithm of the number of the documents in the corpus divided by the number of documents that are specific to the term. The basic idea of TF-IDF is to determine term weight that are frequent in the document (using the TF metric), but infrequent in the corpus (using the IDF metric).

The term frequency (i.e., TF) for sky in  $d_1$  is then 1. The word sky appears in two documents. Then, the inverse document frequency (i.e., IDF) is calculated as  $\log\left(\frac{4}{2}\right) = 0.301$ . Thus, the TF-IDF weight is the product of these quantities:  $1 \times 0.301 = 0.301$ .

The main drawback of TF-IDF is the fact that it unsupervised method; it does not take into account the distribution of class label.

Since the traditional TF-IDF (term frequency-inverse document frequency) is not fully effective for text classification. Several various of TF-IDF based on supervised methods have been proposed in the literature. These variants introduce a new statistic model: feature selection models to measure the term's distinguishing power in a class.

#### 2.2 Supervied Methods Term Weighting

By considering the deficiencies of TF-IDF, researchers have proposed supervised term weighting schemes (STW) [4]. Otherwise, weighting a term by using an information known by the classes. The distribution of a term in different category is described with a contingency table shown in Table II.

TABLE II. THE CONTINGENCE TABLE INFORMATION

Class	$c_k$	$\overline{c}_k$	
$t_i$	A	В	
$\overline{t_j}$	C	D	

A denotes the number of documents belonging to category  $c_k$  where the term  $t_j$  occurs at least once; B denotes the number of documents not belonging to category  $c_k$  where the term  $t_j$  occurs at least once; C denotes the number of documents belonging to category  $c_k$  where the term  $t_j$  does not occur; D denotes the number of documents not belonging to category  $\overline{c_k}$  where the term  $t_j$  does not occur. The contigence table shows that:

- if term  $t_j$  is highly relevant to category  $c_k$  only, which basically indicates that it is a good feature to represent category  $c_k$ , then the value of  $\frac{A}{B}$  tends to be higher.
- if the value of  $\frac{A}{c}$  is larger, which means that the number of documents where term  $t_j$  occurs are greater than the documents where term  $t_j$  does not occur in class  $c_k$ .
- if term  $t_j$  is highly relevant to category  $\overline{c}_k$  only, which basically indicates that it is a good feature to represent category  $\overline{c}_k$ , then the value of  $\frac{B}{A}$ : tends to be higher.
- if the value of  $\frac{B}{D}$  tends to be higher, which means the number of documents where term  $t_j$  occurs are greater than the documents where term  $t_j$  does not occur in class  $\overline{c}_k$ .
- The product of  $\frac{A}{B}$  and  $\frac{A}{C}$  indicates terms  $t_j$ 's relevance with respect to a specific category  $c_k$ . On the other hand, the product of  $\frac{B}{A}$  and  $\frac{B}{C}$  indicates terms  $t_j$ 's relevance with respect to a specific category  $\overline{c}_k$ .

In [4], combining the term frequency and  $\chi^2$  statistic, authors introduce the TF-Chi2 weight of term  $t_i$ :

$$w(t_j, c_k) = t f_{ij} \times \frac{N \times (A \times D - B \times C)^2}{(A+B) \times (C+D) \times (A+C) \times (B+D)}$$
 (2)

In TF.Chi2, the weight of a term is specific to the  $c_k$  category, i.e. it depends on the contribution of the term in the  $c_k$  category. But, the size of the positive class is often smaller than that of the negative counterpart. The Chi2 statistic is limited in the case of multi-class classification, because it is a bi-class schema, hence causes performance loss of classifier. In addition to the drawbacks listed above, the terms informations in the corpus have not been considered [3].

The Measure of Relevance and Distinction with the AD metric[5] is frequently used as a criterion in the field of machine learning. It is based on the notion of relevance of characteristic from the distribution of terms in the category  $c_k$ . The more a term contributes to the distinction of category  $c_k$ , the higher its relevance is in  $c_k$ . AD of a feature  $t_j$  toward a category  $c_k$  can be defined as follows:

$$w(t_j, c_k) = \frac{A}{B} \times \frac{A}{C} \times \left(\frac{A}{B} \times \frac{A}{C} - \frac{B}{A} \times \frac{B}{C}\right)$$
 (3)

In AD metric, only the known information of the category is considered, it ignores the contribution of the terms in the corpus [4] and constitutes a method to bi-class. In the case of multi-class classification some category may not be taken into account because are all group in  $c_k$ .

The work in [6], proposed a term frequency based on weighting scheme using naïve bayes (TF-RTF). It considered the binary text classification case (for a document, d, and its label,  $c_k$ , let  $c_k=1$  denote the positive class, and  $\overline{c}_k=0$  the negative one) and calculated the weight of a term from the posterior probability of each class:

$$w(t_j, c_k) = Nu * | log \frac{(M1u+1)}{(M0u+1)} + log \frac{(M0+p)}{(M1+p)} |$$
 (4)

Where  $N_u$  is the term frequency of a word  $w_u$  in the document;  $M_{1u}$ ,  $M_{0u}$  are the term frequencies of  $w_u$  respectively in the positive class and negative class;  $M_1$ ,  $M_0$  are respectively the total term frequencies in the positive class and negative class;  $\log \frac{(M0+p)}{(M1+p)}$ , is the ratio of total term frequencies. Like all probability patterns, TF-RTF can cause a loss of information in multi-class categorization.

As others proposed metrics, the Information Gain [7] of a given feature  $\mathbf{t}_j$  with respect to class  $c_k$  is the reduction in uncertainty about the value of  $t_j$  when we know the value of  $c_k$ . The more Information Gain is high for a feature, the more important a feature is for the text categorization. Information Gain of a feature  $t_j$  toward a category  $c_k$  can be defined as follows:

$$w(t_j, c_k) = \sum_{c \in \{c_k \ \overline{c}_k\}} \sum_{t \in \{t_j \ \overline{t}_j\}} P(t_j, c_k) \log \frac{P(t_j, c_k)}{P(c_k) P(t_j)}$$
 (5)

Where  $p(c_k)$  is the fraction of the documents in category cover the total number of documents,  $p(t_j, c_k)$  is the fraction of documents in the category  $c_k$  that contain the word t over the total number of documents.  $p(t_j)$  is the fraction of the documents containing the term  $t_j$  over the total number of documents.

The work presented in [8] (TF-BDC), the relevance of a term in a category is defined from the value of entropy. More the entropy is high, more it appears in several categories, and less discriminating they are. However, higher the concentration of the feature in a  $c_k$  category is, more important its discriminating power is. Conversely, a term with a more or less distribution uniform in the different categories has often smaller entropy.

$$w(t_{j}, c_{k}) = 1 + \frac{\sum_{k=1}^{|c|} \frac{p(t_{j} | c_{k})}{\sum_{k=1}^{|c|} p(t_{j} | c_{k})} log \frac{p(t_{j} | c_{k})}{\sum_{k=1}^{|c|} p(t_{j} | c_{k})}}{log(|C|)}$$
(6)

With  $p(t_j, c_k) = \frac{f(t_j, c_k)}{f(c_k)}$ , where  $f(t_j, c_k)$  denotes the frequency of term  $t_j$  in category  $c_k$  and  $f(c_k)$  denotes the frequency sum of all terms in category  $c_k$ .

**Example:** in TABLE I, the term "sky" has an entropy more higher than the term "sun", but "sun" has a higher discriminant power because it is specific to the category "positive".

Like all feature selection methods, TF-BDC ignores the contribution of terms in the document collection.

In order to overcome the shortcomings of the bi-class schemes, Chen and al. propose Inverse Gravity Moment –*TF-IGM* [9] in

order to explore both the contribution of terms in the classification and the provision of information in corpus. It is defined by:

$$w(t_j, c_k) = tf_{ij} * (1 + \lambda igm(t_j))$$
 (7)

Where  $1+\lambda . igm(t_j)$  denotes the igm based global weighting factor of term  $t_j$  in document  $d_i$ , and  $\lambda \in [5; 9]$  is an adjustable coefficient for keeping the relative balance between the global and the local factors in the weight of a term. The  $igm(t_j)$  is defined as follows:

$$\frac{f_{j1}}{\sum_{r=1}^{m} f_{jr}} \tag{8}$$

Where the frequency  $f_{jr}$  (r=1,2,...,m) usually refers to the class-specific document frequency of the term and  $f_{j1}$  the maximal frequency of the term of the class m (sort in descending order). TF-IGM is a supervised term weighting system (STW) because the global IGM weighting factor depends only on known class information, and the contribution of terms on the corpus is ignored.

Like all the supervised methods studied in this paper, only class information is used to determine the overall factor. However, the relevance of a document di depends on its position relative to the center of gravity Gi. Hence the importance of the terms that constitute it.

# 3. OUR PROPOSED TERM WEIGHTING SCHEME: TF-ICD

In this section, we propose a so-called *ICD* (inertia contribution document) model to measure the class distinguishing power of a term and then put forward a new term weighting scheme, TF-ICD, by combining term frequency (TF) with the ICD measure.

#### 3.1 Problem Definition And Motivations

Let d be a set of labeled documents  $d_i$ , in which class is of a finite number of discrete symbols, each representing a class of the classification problem to be addressed. A document  $d_i$  is represented as a vector of terms  $d_i = \{t_{1i},...,t_{ri}\}$  where r is the cardinality of the dictionary  $\{t_1,...,t_n\}$ , and  $0 < t_{ij} < 1$  represents the contribution of term  $t_j$  to the prediction of class. Thus,  $d_i$  is represented by a matrix  $t_{ij}$ . Non-zero  $t_{ij}$  indicates that term  $t_j$  is contained in  $d_i$ .

The aim of our proposition is to transform the initial corpus d into matrix  $t_{ij}$  such as  $t_{ij}$  outperforms the state-of-the-art term weighting scheme by giving better classifier accuracy:

$$tf - icd(d) = \text{matrix } t_{ij} / f: \{T_1, ..., T_n\} \rightarrow class \text{ is better.}$$

Where *icd* represents our statistical model that measures the information quantity of a document, which reflects the term's class distinguishing power.

# 3.2 Analyzing The Discriminating Power Of A Document

From the multidimensional statistical models a corpus can be presented as an individual-variable as described in the Fig.1.




Figure. 1. matrix  $t_{ij}/f: \{T_1, ..., T_n\}$ 

Where I is all individuals (documents), J is set of variables (terms), and  $t_{ij}$  is frequency of the term j in the document i.

By replacing the contingency table with the probability table, we obtain:




Figure. 2. matrix  $f_{ij}$  / f:  $\{T_1, ..., T_n\}$ 

Where  $f_i$  is margin column and  $f_{ij}$  margin line.

Then a document belonging to a category is discriminatory if its conditional distribution  $(\frac{f_{ij}}{f_i})$  is probability of using the term  $t_j$  knowing that one is interested in the  $c_k$  category) is different from its average conditional distribution  $(\frac{f_{.j}}{n})$  likelihood of using the  $t_j$  term). The higher the independence gap, the lower its weight is and its high inertial contribution  $\lambda_{(di)}$ .

#### 3.3 Inertial Contribution Of A Document-Icd

The inertial contribution is the amount of information that a document provides in a corpus, it depends on the product of two measures: (i) the weight of a document  $d_i$ ; (ii) and its difference to independence.

The weight of a document is the probability of obtaining the document  $d_i$  belonging to the category  $c_k$  and is defined by

$$\frac{f_{i.}}{n} \tag{9}$$

The relevance of a document relies to its distance to the origin of the center of gravity described in Fig. 3.




Figure 3. Distance of a document from the center of gravity.

$$d^{2}_{i^{2}}(i,GI) = \sum_{j=1}^{j=J} \frac{\left(f_{ij} - f_{,j}\right)^{2}}{f_{,j}}$$
 (10)

We thus obtain the inertia contribution of a document  $d_i$  in the corpus, defined by

$$\lambda(d_i) = \frac{fi.}{n} \cdot \sum_{i=1}^{j=J} \frac{(f_{ij} - f_{.j})^2}{f_{.j}}$$
 (11)

The table III presents the inertia distribution by categories and by term

TABLE III. INERTIA DISTRIBUTION BY CATEGORIES AND BY

Class 
$$c_1$$
  $c_2$   $c_k$ 

$$\lambda(c_k) \sum_{\substack{di \in c_1 \\ \lambda(d_i)}} \lambda(d_i) \sum_{\substack{di \in c_2 \\ \{d_i \in c_1\}}} \lambda(d_i) \sum_{\substack{di \in c_2 \\ \{d_i \in 2\}}} \lambda(d_i) \cdots \sum_{\substack{di \in k \\ \{d_i \in k\}}} \lambda(d_i)$$

$$ICD(t_j, c_k) = log_2(1 + \frac{\sum_{\{d_i \in c_k\}\{t_{ij \neq 0}\}} \lambda(d_i)}{N_j})$$
 (12)

Where  $\sum_{\{d_i \in c_k\}} \{t_{ij\neq 0}\} \lambda(d_i)$  is the sum of the inertia of documents  $d_i$  of category  $c_k$  containing  $t_j$  and  $N_j$  is the number of documents  $d_i$  of category  $c_k$  containing  $t_j$ 

#### 3.4 Term Weighting By Tf-Icd

The weight of a term in a document should be determined by its importance in the corpus and its contribution to text classification, which correspond respectively to the local and global weighting factors in term weighting. A term's contribution to text classification depends on its class distinguishing power, which is reflected by its contribution of documents inertia. Higher the inertia is, greater term weighting is important. This last can be measured by the ICD metric. Hence, instead of the traditional IDF factor, a new global factor in term weighting is defined based on the ICD metric of the term, as shown in (12). Therefore, the TF-ICD weight

of term  $t_j$  in document  $d_i$  is the product of the TF-based local weighting factor and the ICD-based global weighting factor, i.e.,  $w(t_i, c_k) = tf_{ij} \times ICD(tj, c_k)$ , which is expressed as (13)

$$w(t_j, c_k) = t f_{ij} \times log_2 \left(1 + \frac{\sum_{\{d_i \in c_k\} \{t_{ij \neq 0}\}} \lambda(d_i)}{N_i} \right)$$
 (13)

#### 4. EXPERIMENTS

We used the sms spam collection data [3]. This collection is composed by 4,827 legitimate messages and 747 mobile spam messages, 5,574 short messages. Table 5 shows its basic statistics.

TABLE IV. BASIC STATISTICS.

Class	Amount	%
Hams	4,827	86.60
Spams	747	13,40
Total	5,574	100

After applying our term weighting scheme, we have tested three well-known data mining algorithms on the transformed corpus. Table IV shows the effectiveness of our term weighting algorithm for text classification. The classification accuracies obtained by successively applying SVM, DT and LR algorithms on our term weighting representation are better than those obtained on TF-IDF and TF-IGM.

TABLE V. BASIC STATISTICS.

Classification accuracy				
tf-icd	tf-igm	tf-idf		
0.8829	0.8779	0.8756		
0.9354	0.9292	0.9297		
0.8836	0.8787	0.8763		
	tf-icd 0.8829 0.9354	tf-icd tf-igm  0.8829 0.8779  0.9354 0.9292		

#### 5. CONCLUSION AND PERSPECTIVES

In this paper, we studied the term weighting scheme issue. We proposed an efficient term weighting scheme based on inertia contribution of a document.

The test results of text classification show their convincible efficiency. We plan in our future work to conduct our algorithm on others benchmarks data sets.

#### 6. REFERENCES

- [1] Xue DejunSun Maosong. Chinese Text Categorization Based on the Binary Weighting Model with Non-binary Smoothing. European Conference on Information Retrieval ECIR 2003: Advances in Information Retrieval pp 408-419
- [2] Man Lan, Chew Lim Tan, Jian Su, and Yue Lu. Supervised and traditional term weighting methods for automatic text categorization. Pattern Analysis and Machine Intelligence, IEEE Transactions on, 31(4):721–735, 2009.

- [3] Z. Deng, S. Tang, D. Yang, M. Zhang, L. Li, K. Xie, A comparative study on feature weight in text categorization, Springer Berlin Heidelberg, Hangzhou, China, 2004.
- [4] Franca Debole, Fabrizio Sebastiani. Supervised term weighting for automated text categorization. Proceedings of the 2003 ACM symposium on Applied computing. (pp 784-788).
- [5] Jieming Yang, Jing Wang, Zhiying Liu, Zhaoyang Qu. A Term Weighting Scheme Based on the Measure of Relevance and Distinction for Text Categorization. International Conference on Advanced Computing Technologies and Applications (ICACTA-2015) (pp 13-22). doi: 10.1016/j.procs.2015.03.074
- [6] Guozhong Feng, Han Wang, Tieli Sun, and Libiao Zhang. A Term Frequency Based Weighting Scheme Using Naïve Bayes for Text Classification. Journal of Computational and Theoretical Nanoscience (pp 319-326) 2016. DOI: 10.1166/jctn.2016.4807
- [7] Tao Wang, Yi Cai, Ho-fung Leung, Zhiwei Cai and Huaqing Min. EntropybasedTermWeightingSchemesforTextCategorizationinVSM . 2015 IEEE 27th International Conference on Tools with Artificial Intelligence. 10.1109/ICTAI.2015.57 (12 pg)
- [8] Tatsunori Mori Miwa Kikuchi Kazufumi Yoshida. Term Weighting Method based on Information Gain Ratio for Summarizing Documents retrieved by IR systems. Journal of Natural Language Processing, 9(4):3—32. September 2001
- [9] Kewin Chen, Zuping Zhang, Jun Long, Hao Zhang: Turning from TF-IDF to TF-IGM for term weighting in text classification. In journal Expert Systems with Applications, vol. 66 Issue C, December 2016, pp. 245-260.
- [10] Cormack, G. V., Gómez Hidalgo, J. M., and Puertas Sánz, E. 2007. Spam filtering for short messages. In Proceedings of the Sixteenth ACM Conference on Conference on information and Knowledge Management (Lisbon, Portugal, November 06 - 10, 2007). CIKM '07. ACM, New York, NY, 313-320. DOI= http://doi.acm.org/10.1145/1321440.1321486
- [11] Ji Geng, Yunling Lu, Wei Chen, Zhiguang Qin. An improved text categorization algorithm based on VSM. 2014 IEEE 17th International Conference on Computational Science and Engineering. DOI 10.1109/CSE.2014.313
- [12] Haibing Wu, Xiaodong Gu, Yiwei Gu. Balancing between over-weighting and under-weighting in supervised term weighting. Information Processing and Management 53 (2017) 547–557. http://dx.doi.org/10.1016/j.ipm.2016.10.003
- [13] Payam Karisani, Maseud Rahgozar, Farhad Oroumchian. A query term re-weighting approach using document similarity. Information Processing & Management Volume 52, Issue 3, May 2016, Pages 478-489. https://doi.org/10.1016/j.ipm.2015.09.002
- [14] Mounia Haddoud, Aïcha Mokhtari, Thierry Lecroq · Saïd Abdeddaïm. Combining supervised term-weighting metrics for SVM text classification with extended term representation. Springer-Verlag London 2016 Knowl Inf Syst DOI 10.1007/s10115-016-0924-1